





0120



0150



0200



0330




0390



0410




0450



0570



0740



0780



0950



0980

# SAHCO

1831

## Baru

Type: Upholstery

*In accordance with California AB2998 or similar regulation in other states of North America, this product should not be used for upholstery in USA*

Composition: 3% polyamide, 10% polyester, 87% wool

Yarn type: Worsted

Binding: Sateen Boucle

Width: Approx. 140 cm, 55 inches

Weight: Approx. 700 g/lin.m, 25 oz/ly

Repeat: None

Foreign fibers may occur in light colours

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week.

Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. Extraction cleaning might dissolve water based glue. Pay attention to temperature and amount of cleaning fluid.

Disinfection, see [www.kvadrat.dk/en/sahco](http://www.kvadrat.dk/en/sahco)



10<sup>year</sup>  
warranty



## Abrasion

Approx. 65.000 Martindale rubs, EN ISO 12947

*Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention*

## Pilling

Note 5, EN ISO 12945

## Seam slippage

Seam parallel to warp: 2.0 mm  
parallel to weft: 7.0 m

## Snagging

Garde 1 ICI Testmethod FAB 29, Tumble-Box

## Lightfastness

Note 4-6 ISO 105-B02

## Fastness to rubbing

Dry note 4 ISO 105-X12

Wet note 3-4 ISO 105-X12

## Flame resistance

BS 5852 Crib 5 with treatment \*

BS 5852 Part 1

EN 1021-1/2

US Cal. Bull. 117-2013

*\* To pass this test flame retardant treatment is necessary. We are looking into more environmental friendly alternatives but for now the external finisher may use a treatment containing halogen based flame retardants.*

# SAHCO

1831

## **ACT Guidelines Woven fabrics**

### **Flammability**

US Cal. Bull. 117-2013

### **Dry & Wet Crocking AATCC 8**

Dry Crocking: Grade 4.5

Wet Crocking: Grade 4.5

### **Colour Fastness to Light AATCC 16**

Grade 4.5 minimum 40 hours

### **Physical properties**

Pilling ASTM D3511 Class 4

Seam Slippage ASTM D4034 warp 12 / weft 19 lbs

### **Abrasion ASTM D4966**

65.000 cycles Martaindale – High Traffic

### **Benefits of wool**

Wool is a renewable resource

Wool is very comfortable because of its ability to absorb/  
give off humidity

Wool is flame retardant

Wool is biodegradable

Wool is naturally soil resistant

Wool ages with grace

### **Quality benefits**

Complies with Möbelfakta

Very good abrasion

Very good lightfastness

Flame retardant / Permanent flame retardant

Washable

### **Environmental benefits**

Follow the EU Ecolabel dye restrictions incl. AZO dye  
and heavy metal restrictions

No use of halogen based flame retardants (incl. brominated  
and chlorinated)

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

### **Green building certificates**

Greenguard Gold: Low chemical emission

Environmental Product Declaration (EPD): Based on a  
Health Product Declaration (HPD): Declaring textile  
content and substance

### **Country of origin**

Norway

### **Launch**

2021

### **Warranty**

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard  
material is FSC certified and / or contains recycled  
content.

For further information

[www.kvadrat.dk/en/sahco](http://www.kvadrat.dk/en/sahco)